

# Uniview™

## Uniview – Solar protection with a view.

Uniview 1000, 3000 and 3100 fabrics are designed to satisfy the highest technical and aesthetic standards as demanded by today's residential, commercial, educational and healthcare applications. Providing the best in transparent solar shading solutions, Uniview fabrics are physically strong, washable and will not fray. Fabric is fire retardant, non-toxic, UV resistant and is both bacteria and fungal resistant.

UNIVIEW SPECIFICATION			
SERIES	1000	3000	3100
Useable Width	1.83m/2.5m	1.83m/2.5m	1.83m/2.5m
Roll Length	27.4m	30m	30m
Composition	25% Polyester, 75% Vinyl on polyester	30% Polyester, 70% Vinyl on polyester	25% Polyester, 75% Vinyl on polyester
Mesh/In	52 x 16"	48 x 48"	52 x 48"
Mesh Weight	690 g/m <sup>2</sup>	410 g/m <sup>2</sup>	510 g/m <sup>2</sup>
Yarn diameter	0.020 x 0.020"	0.013 x 0.013"	0.013 x 0.013"
Thickness	1.00mm	0.60mm	0.70mm
Breaking Strength	300 x 300 lbs ASTM D5035	330 x 330 lbs ASTM D5035	330 x 330 lbs ASTM D5035
Abrasion Resistance	> 10000 (ASTM D4966)	> 10000 (ASTM D4966)	> 10000 (ASTM D4966)
Flame Retardant	Grade B1 (GB 8624-1997)	BS 5867:1980 Part 2 Type B	Grade B1 (GB 8624-1997)
Openness Factor	1%	3%	3%
UV Blockage	Approx. 99%	Approx. 95%	Approx. 97%